

Jul.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C(NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C
	VOLTAGE	100 V AC	APPLICABLE CONNECTOR	DF19#-*P-1H(56)
	CURRENT	0.5 A		
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="radio"/>	<input type="radio"/>
MARKING	CONFIRMED VISUALLY.		<input type="radio"/>	<input type="radio"/>
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
<input type="checkbox"/>				
REMARKS		APPROVED	TY.OMA	06.02.09
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.		CHECKED	HK.UMEHARA	06.02.09
		DESIGNED	IO.DENPOUYA	06.01.28
Unless otherwise specified, refer to JIS C 5402.		DRAWN	AH.MIYAZAKI	06.01.28
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-311700-01	
HRS	SPECIFICATION SHEET	PART NO.	DF19G-*S-1F-GND(05)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL685-	<input type="checkbox"/> 1/