APPLICA	BLE STAN	DARD									
	OPERATING TEMPERATURE RANGE		−25°C TO +8	5°C STORAGE TEMPERATUR			RANGE		−25°C TO +60°C		
RATING		NG&STORAGE OTY RANGE	85%MAX	85%MAX APP		PLICABLE CABLE			A CABLE DIAMETER:		7.1
VOLTAGE		DLTAGE				ENT					
SPECIFICATIONS											
IT	EM		TEST METHOD			REQUIREMENTS				QT	АТ
CONSTR		1				,				X	
	KAMINATION		SUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				Х
MARKING		CONFIRMED VISUALLY.								X	Х
COUN	T DE	SCRIPTION OF REVISIONS DIS-E-00003216			DESIGNI				CHECKED	DA	
Z4X 1 REMARK		Z10		KN. ICH	IKAWA APPROV		VED	TU. TANIGUCHI AO. SUZUKI	20201019		
THIS PRODUCT SHALL BE MATED WITH DH40-						S					
OR DH3 * B-17S, IT APPLIES TO DH40-17S DH3 * B-17S ABOUT A MECHANICAL,)R		CHECKED		MO. SHIMOYAMA		0416
ENVIRONMENTAL CHARACTERISTICS.							DESIGNED		D TS. ITO		0416
		specified, refer					DRAWN		TS. 1T0	20090416	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DF	RAWIN	G NO.		ELC-126586-00-00		
נחכ	SI	SPECIFICATION SHEET			PART	NO.		DH-17-CV1B			
HS	HIROSE ELECTRIC CO., LTD.				CODE NO.		Cl	CL244-0009-6-00 🛕 1/1			