

May.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ8.3~9.3	
	CURRENT		VOLTAGE		
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.			X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
2	DIS-E-003060	TM. ONO	KN. ICHIKAWA	09.12.14	
REMARK			APPROVED	AO. SUZUKI	09.04.28
THIS PRODUCT SHALL BE MATED WITH DH3*B-37S, IT APPLIES TO DH3*B-37S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.			CHECKED	KN. ICHIKAWA	09.04.28
			DESIGNED	MO. SHIMOYAMA	09.04.28
			DRAWN	MO. SHIMOYAMA	09.04.28
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		
	SPECIFICATION SHEET		PART NO.	DH-37-CT1B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0041-9-00	1/1