

Apr.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△1	9	RE-5-1840	Y.K.G	A.B.H	17.12.12	△3	2	RE-5-2935	K.C.J	A.B.H	23.01.11
△2	2	RE-5-2287	K.C.J	A.B.H	19.09.11	△4	2	RE-5-3141	K.G.J	Y.W.S	24.04.05

APPLICABLE STANDARD

RATING	OPERATING TEMPERATURE RANGE	-40°C ~ 85°C (NOTE1) △3	STORAGE TEMPERATURE RANGE	-10°C TO 60°C (WITH PACKING) △2 △3
	VOLTAGE	AC 10 V	OPERATING OR STORAGE HUMIDITY RANGE	95% MAX (NON-CONDENSING)
	CURRENT	0.5A		

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT	ACCORDING TO DRAWING	X	X
MARKING			X	X

ELECTRICAL CHARACTERISTICS

CONTACT RESISTANCE MILLIVOLT LEVEL METHOD IEC60512-2-1	100mA MAX (DC or 1000Hz) △4	INITIALLY 100mΩ MAX (NOTE2)	X	-
INSULATION RESISTANCE IEC60512-3-1 △1	MEASURE WITHIN 1 MINUTE AFTER APPLYING 500V DC	INITIALLY 1000MΩ MIN	X	-
VOLTAGE PROOF IEC60512-4-1 △1	500Vrms AC IS APPLIED FOR 1 MINUTE	① NO FLASHOVER OR BREAKDOWN ② CURRENT LEAKAGE 1mA MAX	X	X

MECHANICAL CHARACTERISTICS

MECHANICAL OPERATION [OFFICE ENVIRONMENT] EIA364B class 1.1	-NANO SIM CARD 5,000 TIMES INSERTION AND WITHDRAWAL SHALL BE MADE AT THE CYCLE RATE LESS THAN 10 CYCLES PER 1MINUTE -MICRO SD CARD 10,000 TIMES INSERTION AND WITHDRAWAL SHALL BE MADE AT THE CYCLE RATE LESS THAN 10 CYCLES PER 1MINUTE NOTE : AFTER EACH 10 CYCLES STOP THE INSERTION AND REST THE CONNECTOR FOR 5 TO 10 MINUTES. CARD SURFACE SHALL BE CLEANED BY AIR BLOW: AT EACH 100 CYCLES INTERVAL(10 TIMES) FROM START TO 1,000 CYCLES. AT EACH 1,000 CYCLES INTERVAL(9 TIMES) FROM 1,001 CYCLES TO 10,000 CYCLES.	① CONTACT RESISTANCE: AFTER TEST 50mΩ MAX CHANGE ② NO MECHANICAL DAMAGE SHALL OCCUR ON THE PARTS.	X	-
CARD INSERTION FORCE	MEASURED BY APPLICABLE CARD AT 25± 3mm/min	1N TO 7N (NOTE3)	X	-
CARD EJECTION FORCE				
VIBRATION AND HIGH FREQUENCY IEC60512-6-4 △1	FREQUENCY 10 TO 55 TO 10 Hz/min, SINGLE AMPLITUDE 0.75mm FOR 4h IN X,Y,Z 3 DIRECTIONS, TOTAL 12h	① NO ELECTRICAL DISCONTINUITY OF 1us ② NO MECHANICAL DAMAGE SHALL OCCUR ON THE PARTS.	X	-
SHOCK IEC60512-6-3 △1	ACCELERATION 490m/s ² STANDARD HOLDING TIME 11ms, SEMI-SINE WAVE FOR 3 TIMES IN 3 DIRECTIONS, TOTAL 18 TIMES.	③ CONTACT RESISTANCE AFTER TEST 50mΩ MAX CHANGE	X	-

REFERENCE DRAWING

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
(NOTE1) : INCLUDE THE TEMPERATURE RISE BY CURRENT (NOTE2) : CONTACT RESISTANCE INCLUDES CONDUCTOR RESISTANCE UNLESS OTHERWISE SPECIFIED, THE TEST SHOULD BE DONE UNDER TEMP 15 TO 35°C. AIR PRESSURE 86 TO 106kPA, RESLATIVE HUMIDITY 25 TO 85%. (NOTE3) : IT MAY BE CHANGED ACCORDING TO THE TRAY/CARD MATERIAL AND DIMENSIONS.	J.Y.JUNG 16.08.08	J.Y.JUNG 16.08.08	B.H.AN 16.08.08	H.C.SONG 16.08.08	ENG 24.04.11 DEPT

NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST


HIROSE KOREA CO.,LTD.	SPECIFICATION SHEET	PART NO. KP15B-6S-SF(800)
CODE NO.(OLD) CL	DRAWING NO. ELC4-631968	CODE NO. CL 6538-0005-8-800

1/2

Apr.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
ENVIRONMENTAL CHARACTERISTICS				
RAPID CHANGE OF TEMPERATURE IEC60512-11-4 △₁	5 CYCLES(1CYCLE=1HOUR) WITH CARD MATED CONDITION (TEMPERATURE : -55℃ TO 85℃ , RELOCATION TIME TO CHAMBER : WHITIN 5MIN)		X	-
DRY HEAT IEC60512-11-9 △₁	EXPOSED AT 85℃ FOR 96 HOURS WITH CARD MATED CONDITION	① CONTACT RESISTANCE : AFTER TEST 50mΩ MAXCHANGE	X	-
COLD IEC60512-11-10 △₁	EXPOSED AT -40℃ FOR 96 HOURS WITH CARD MATED CONDITION	② INSULATION RESISTANCE : AFTER TEST 100MΩ MIN	X	-
DAMP HEAT STEADY STATE IEC60512-11-3 △₁	EXPOSED AT 40℃ , 80% , 96 HOURS WITH CARD MATED CONDITION	③ NO MECHANICAL DAMAGE OR HEAVY CORROSION SHALL OCCUR ON THE PARTS.	X	-
CORROSION SALT MIST IEC60068-2-11 △₁	EXPOSED AT 35±2℃ , 5% SALT WATER SPRAY FOR 48Hr		X	-
RESISTANCE TO SOLDERING HEAT △₄	SEE THE FOLLOWING CONDITION, NUMBER OF CYCLE 1 TIME (NOTE4)	NO MECHANICAL DAMAGE OR HEAVY CORROSION SHALL OCCUR ON THE PARTS. △₂	X	-



REFERENCE DRAWING

NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST

HIROSE KOREA CO.,LTD.	SPECIFICATION SHEET	PART NO. KP15B-6S-SF(800)
CODE NO.(OLD) CL	DRAWING NO. ELC4-631968	CODE NO. CL 6538-0005-8-800
		2/2