APPLICA	BLE STAN	DARD								
	OPERATING TEMPERATURE RANGE		-10°C ~ 60°C		STORAGE TEMPERATU	TORAGE EMPERATURE RANGE		-10°C ~ 60°C		
RATING	POWER				CHARACTER	RISTIC				
	1 0 1 2 1 1		SPECI		IMPEDANCE					
ļ				FICAT		DE	OLUDEM	ENTO	QT	Τ , -
	RUCTION		TEST METHOD			KE	QUIREM	EN12	Q1	AT
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCOR	DING TO DE	RAWING.		X	X
MARKING		CONFIRMED VISUALLY.							X	X
COUN	T D	ESCRIPTI	ON OF REVISIONS	DE	SIGNED		С	HECKED	DA	TE
REMARK						APPROVE		HO. MIWA	06. 1	
						CHECKE		SJ. SHIMIZU	06. 1	
Unless otherwise aposition refer to US			ofor to IIC C E400			DESIGNE		TS. ITO		2. 08
Unless otherwise specified, refer to JIS C 5402.				.				TS. 1T0		2. 08
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				t	DRAWIN	RAWING NO. ELC4-025739-01			9-01	
HS	SI	PECIFI	CATION SHEET	ATION SHEET PA		TM-4-DC1				
117			ECTRIC CO., LTD.		DDE NO.	CL222-1364-6-00			\wedge	1/1