APPLICABLE STANDARD															
RATING		OPERATING TEMPERATURI	E RANGE	-25 °C TO 60 °C	2		RAGE PERATUI	RE RAN	GE [1>	-25 °C TO	60 '	°C ∠	2	
KATING		VOLTAGE	CURENT												
SPECIFICATIONS															
	ITE	M		TEST METHOD				REQUIREMENTS QT AT							
CONSTRUCTION															
GENERAL EXAMINATION			VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING. X							Х	
MARKING			CONFIRMED VISUALLY.									Χ	Χ		
_	OUNT	DE	DESCRIPTION OF REVISIONS			DESIGNED				CHECKED			DATE		
2		DIS-E-00002227			TS. I					TANIGUCHI		2019			
REMARK 1 > PACKING M			ATERIAL IS NOT INCLUDED.				<u> </u>	APPROVI					20050105		
'-'	ı ا	ACKING IVI	ATERIAL IS NOT INCLUDED.				-	CHECKED			TH. KAMEYA		20050105		
Unless otherwise specified refer to US C 5402							}	DESIGNED		SS. SATOH			20050105		
Unless otherwise specified, refer to JIS C 5402. Note QT:Qualification Test AT:Assurance Test X:Applicable Test							DRAWN			SS. SATOH 200501 ELC4-121484-03				U1U5	
			rest		DRAWING NO. ELC4-1214 PART NO. TM21P-88P (22)				,4 [–] U3						
R	ל			CATION SHEET LECTRIC CO., LTD)_	CODE NO		Cl 223		2-2862-9-22			<u>\$</u>	1/1	
11113				,	-		- 110.	J						., .	