

Sep.1.2021 Copyright 2021 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE	-40 °C TO +90°C(90%RH MAX)	STORAGE TEMPERATURE RANGE	-20°C TO +70°C(90%RH MAX)		
	POWER	-w	CHARACTERISTIC IMPEDANCE	50 Ω (0 TO 6 GHz)		
	PECULIARITY	----	RECEPTACLES	X.FL-R-SMT-1		
SPECIFICATIONS						
ITEM	TEST METHOD		REQUIREMENTS	QT	AT	
CONSTRUCTION						
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.			-	-	
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	10 mA MAX (DC OR 1000 Hz).		CENTER CONTACT	25 mΩ MAX.	X	-
			OUTER CONTACT	10 mΩ MAX.	X	-
INSULATION RESISTANCE	100 V DC.		500 MΩ MIN.		X	-
VOLTAGE PROOF	200 V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX.		NO FLASHOVER OR BREAKDOWN.		X	-
VOLTAGE STANDING WAVE RATIO	FREQUENCY 0.045 TO 3 GHz.		VSWR	1.3 MAX.	X	-
	FREQUENCY 3 TO 6 GHz.		VSWR	1.5 MAX.		
INSERTION LOSS	FREQUENCY ---- TO ---- GHz		---- dB MAX.		-	-
MECHANICAL CHARACTERISTICS						
CONTACT INSERTION AND EXTRACTION FORCES	φ 0.34 ± 0.002 BY STEEL GAUGE.		INSERTION FORCE	---- N MAX.	-	-
			EXTRACTION FORCE	0.1 N MIN.	X	-
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE	30 N MAX.	X	-
			EXTRACTION FORCE	3N TO 20N	X	-
MECHANICAL OPERATION	20 TIMES INSERTIONS AND EXTRACTIONS.		1) CONTACT RESISTANCE: CENTER CONTACT 30 mΩMAX. OUTER CONTACT 15 mΩMAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
VIBRATION	FREQUENCY 10 TO 100 Hz SINGLE AMPLITUDE 1.5 mm, 59 m/s ² AT 5 CYCLES FOR 3 DIRECTIONS.		1) NO ELECTRICAL DISCONTINUITY OF 1μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
SHOCK	735 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.				X	-
CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)	APPLYING A PULL FORCE THE CABLE AXIALLY AT N MAX.		1) NO WITHDRAWAL AND BREAKAGE OF CABLE. 2) NO BREAKAGE OF CLAMP.		-	-
ENVIRONMENTAL CHARACTERISTICS						
DAMP HEAT	EXPOSED AT 40 °C, 95 % TOTAL 96 h		1) INSULATION RESISTANCE: 10 MΩ MIN. (AT HIGH HUMIDITY) 2) INSULATION RESISTANCE: 500 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -40 → 5-35 → +90 → 5-35°C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.		NO HEAVY CORROSION.		X	-
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE	
0						
REMARK RoHS COMPLIANT			APPROVED	MH. YAMANE	13. 05. 08	
Notes 1. The quantity of this product is 10000 connectors per reel.			CHECKED	MH. TSUCHIDA	13. 05. 07	
② VSWR was mounted to a 50Ω glass epoxy board and measurements were conducted with SMA conversion adapters attached.			DESIGNED	TS. SAWAI	13. 04. 23	
Unless otherwise specified, refer to JIS C 5402.			DRAWN	TS. SAWAI	13. 04. 23	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-341481-80	
HRS	SPECIFICATION SHEET		PART NO.	X. FL-PR-SMT1-2 (80)		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL331-0713-7-80	0	1/1