





APPLICABLE STANDARD		USB2.0 SPECIFICATION AND MICRO-USB CABLE AND CONNECTORS SPECIFICATION.					
RATING	OPERATING TEMPERATURE RANGE	-30℃ TO +85℃	STORAGE TEMPERATURE RANGE	-30℃ TO +60 ℃ 			
	VOLTAGE	30 V AC	CURRENT	SIGNAL ONLY	1.0 A/pin		
				POWER APPLY	1.8 A/pin (PIN No.1,No.5) 0.5 A/pin (PIN No.2-No.4)		
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.				X	X
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).		30 mΩ MAX.		X	X
INSULATION RESISTANCE		500 V DC.		100 MΩ MIN.		X	X
VOLTAGE PROOF		100 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X	X
CAPASITANCE		MEASURE ADJACENT TWO CONTACTS AT 1000±10 Hz AC VOLTAGE.		2 pF MAX.		X	—
MECHANICAL CHARACTERISTICS							
INSERTION AND WITHDRAWAL FORCES		A MAXIMUM RATE OF 12.5 mm/min. MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE 35 N MAX. WITHDRAWAL FORCE 8 N MIN.		X	—
MECHANICAL OPERATION		10000 TIMES INSERTIONS AND EXTRACTIONS. MATING SPEED - MECHANICALLY OPERATED: 500 CYCLES / h OR - MANUALLY OPERATED: 200 CYCLES / h		1) CONTACT RESISTANCE: NO INCREASE OF MORE THAN 10 mΩ FROM INITIAL VALUE. 2) INSERTION FORCE 35 N MAX. WITHDRAWAL FORCE 8 N MIN. 3) NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		X	—
VIBRATION		FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, AT 2h FOR 3 AXIAL DIRECTIONS, TOTAL 6h.		1) NO ELECTRICAL DISCONTINUITY OF 1 μs. 2) NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		X	—
RANDOM VIBRATION		FREQUENCY 50 TO 2000 Hz AT 15 min FOR 3 AXIAL DIRECTIONS.				X	—
SHOCK		490m/s ² DURATIONS OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS, TOTAL 18 TIMES.				X	—
ENVIRONMENTAL CHARACTERISTICS							
THERMAL SHOCK		TEMP -55 →+15 TO +35→+85→+15TO+35 ℃ TIME 30 → 2 TO 3 → 30→ 2 TO 3 min UNDER 10 CYCLES. (MATING APPLICABLE CONNECTOR)		1) CONTACT RESISTANCE: 70 mΩ MAX. 2) INSULATION RESISTANCE: 10 MΩ MIN. 3) NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		X	—
HUMIDITY LIFE		TEMPERATURE -10~65 ℃, HUMIDITY 90 TO 98 %, UNDER 7 CYCLES (168 h) (MATING APPLICABLE CONNECTOR)		NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		X	—
DRY HEAT		EXPOSED AT +85±2 ℃ , 96 h. (MATING APPLICABLE CONNECTOR)		NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		X	—
COLD		EXPOSED AT -40±2 ℃ , 96 h. (MATING APPLICABLE CONNECTOR)		NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.		X	—
CORROSION SALT MIST		EXPOSED AT 5 % SALT WATER, 35 ℃, FOR 48h. (LEFT UNDER UNMATED CONDITION.)		NO HEAVY CORROSION.		X	—
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	DATE
	1	DIS-E-00010987		KG. OKITA		MN. KENJO	20220829
REMARK HIROSE will not guarantee the performance on these specifications in case this product will be mated with the others which is not HIROSE's. Unless otherwise specified, refer to USB2.0, EIA364 or IEC 60512.				APPROVED	NM. NISHIMATSU		20151027
				CHECKED	KN. ICHIKAWA		20151027
				DESIGNED	TS. ITO		20151027
				DRAWN	AK. AKIYAMA		20151027
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC-126332-33-00	
	SPECIFICATION SHEET			PART NO.		ZX62-B-5PA (33)	
	HIROSE ELECTRIC CO., LTD.			CODE NO.		CL0242-0033-8-33	 1/2

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
SOLDERABILITY	SOLDERING POINT IMMersed IN SOLDER BATH OF 255±5°C, 5 sec. (USING TYPE R FLAX)	SOLDER SHALL COVER MINIMUM OF 95% OF THE SURFACE BEING IMMersed	X	—
RESISTANCE TO SOLDERING HEAT	A PROFILE IS SHOWN IN FIG-1, UNDER 2 CYCLES.	NO DEFORMATION OR SIGNIFICANT LOOSENESS OF CONTACTS.	X	—




FIG - 1 RESISTANCE TO SOLDERING HEAT
(TEMPERATURE AT TOP SURFACE OF CONNECTOR)

RECOMMENDED PROFILE REFERS TO FIG – 2.
(TEMPERATURE AT SMT LEADS)




FIG - 2 RECOMMENDED REFLOW PROFILE TEMPERATURE

Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC-126332-33-00	
HRS	SPECIFICATION SHEET	PART NO.	ZX62-B-5PA (33)		
	HIROSE ELECTRIC CO., LTD.	CODE NO	CL0242-0033-8-33	△	2/2