

Jul.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△ 4	DIS-E-001408	M.S	K.I	07.3.27	△				
△					△				
APPLICABLE STANDARD		USB2.0 SPECIFICATION AND △ MICRO-USB CABLES AND CONNECTORS SPECIFICATION							
RATING	OPERATING TEMPERATURE RANGE	△-30 °C TO +85 °C			STORAGE TEMPERATURE RANGE	△-30 °C TO +85 °C			
	VOLTAGE	-			OPERATING HUMIDITY RANGE	- % TO - %			
	CURRENT	-			APPLICABLE CABLE	-			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×	×
MARKING		CONFIRMED VISUALLY.						×	×
REMARKS △ HIROSE will not guarantee the performance on these specifications in case this product will be mated with the others which is not HIROSE's.					DRAWN M.SHIMOYAMA 07.2.1	DESIGNED M.SHIMOYAMA 07.2.1	CHECKED R.KOYAMA 07.2.2	APPROVED A.SUZUKI 07.2.5	RELEASED
Unless otherwise specified, refer to USB2.0 or EIA364									
Note QT:Qualification Test AT:Assurance Test X:Applicable Test									
HS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET			PART NO. ZX64-B-SLDC	
CODE NO.(OLD) CL		DRAWING NO. ELC4-126125			CODE NO. CL242-0018-4			1/1	