
Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS DRAWING FOR REFERENCE

NOTES 1 THE RECOMMENDED CLAMP TORQUE, REF.NO. ④AND ⑩ : 1.5 N·m.
1 THREAD LOCKER TO THE THREADED PORTION OF REF.NO. ① APPLIES TO PREVENT REF.NO. ④ FROM LOOSING.
RECOMMENDED THREAD LOCKER:LOCTITE 263, HENKEL JAPAN LTD.
REF.NO. ⑩ SHALL BE TIGHTENED BY TORQUE AFTER CLAMPED UNTIL IT TOUCHES THE SURFACE B.
2 ONE EXAMPLE OF THE ROTATION OF REF.NO. ①, ④AND ⑩ IS SHOWN.
1 3 THE ASSEMBLY THIS PRODUCT APPLIES TO THE MANUAL ETAD-C0355-00.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
5	POLYAMIDE				
4	BRASS	MATTE FINISH NICKEL PLATING	10	BRASS	MATTE FINISH NICKEL PLATING
3	BRASS	GOLD PLATING 0.2μm min. NICKEL UNDER PLATING 2μm min.	9	POLYAMIDE	
			8	BRASS	MATTE FINISH NICKEL PLATING
2	POLYAMIDE	(BLUE)	7	STEEL	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATING	6	STAINLESS STEEL	

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1	2	DIS-C-00016940	HT. ZENBA	EJ. KUNII	20240214

HIROSE ELECTRIC CO., LTD.

APPROVED	MR. YOSHIDA	20050105
CHECKED	MO. SATOH	20050105
DESIGNED	YH. YAMADA	20050105
DRAWN	YH. YAMADA	20050105

DRAWING NO.	EDC4-007756-73
PART NO.	HR10-7P-4P(73)
CODE NO.	CL0110-0021-6-73

1 1/1

FORM HC0011-5-51