



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE









Notes 2 1 The recommended clump torque of Ref. No.⑥ to be 0.5N・m.
LOCTITE 263, LOCPRIMER 7649, ROCTITE JAPAN is recommended to prevent Ref. No.⑥ from loosening.
2 Table for soldering is available HR30-6R-6P-T01.
3 Surface plating:gold plating 0.2μm min.
Under plating:nickel plating 2μm min.
2 4 When this connector is mounted on to panel, be careful Ref. No.④ is assembled surely Ref. No.① as shown in this figure to keep waterproof effectiveness.
2 5 The assembly of this product applies to the manual ETAD-C0302-00.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	PPS	(Black)	6	Brass	Nickel plating
2	Brass	3	5	Phosphor bronze	Nickel plating
1	PPS	(Black) UL94V-0	4	CR	(Black)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	2	4	DIS-C-00014886	HY. KISHI	HY. KOBAYASHI	20230328

HIROSE ELECTRIC CO., LTD.

APPROVED	MR. YOSHIDA	20050105
CHECKED	MO. SATOH	20050105
DESIGNED	YH. YAMADA	20050105
DRAWN	YH. YAMADA	20050105

DRAWING NO. EDC3-112023-71
PART NO. HR30-6R-6P(71)
CODE NO. CL0130-1009-0-71
2 1/1