

THE RECOMMENDED ADHESIVE AND PRIMER OF REF NO. ①:LOCTITE 243 AND LOCK PRIMER 7649 MADE BY HENKEL JAPAN LTD.

3 ROTATION EXAMPLE ARE SHOWN FOR REF. NO. ①. ③. ⑧. AND ①.

- 4 APPLICABLE CRIMP CONTACT: HR34B-SC1-211(CL134-0050-4) APPLICABLE WIRE: AWG#20 TO AWG#24(COVERED WIRE MAX, OUTSIDE DIA.  $\phi$  1.7) APPLICABLE CONTACT REMOVAL TOOL(EXTRACTION TOOL):RP6-SC-TP(CL150-0039-0)
- 5 THE CABLE PULL AND TWISTING STRENGTH AND OTHER CHARACTERISTICS MAY DIFFER, DEPENDING ON THE CABLE STRUCTURE. PLEASE CONFIRM BEFORE THE USE.

	6	ACRYLONITORILE BUTADIENE RUBBER	(BLACK)						
	5	PHOSPHOR BRONZE	NICKEL PLATING	11	POLYPHENY	LENE SULFIDE	(BLACK) UL94V-0		
	4	STAINLESS STEEL		10	POLYAM	OLYAMIDE (WHITE) UL94V-0			
	3	ZINC ALLOY	NICKEL PLATING	9 HYDROGENATION ACRYLONITRILE BUTADIENE RUBBER 8 ALUMINIUM ALLOY		(BLACK)			
	2	ZINC ALLOY	NICKEL PLATING			[UM ALLOY	NICKEL PLATING		
Ī	1	POLYPHENYLENE SULFIDE	(BLACK) UL94V-0	7	7 ACRYLONITORILE BUTADIENE RUBBI		(BLACK	)	
	NO.	MATERIAL	FINISH , REMARKS	NO.	MA	MATERIAL		FINISH , REMARKS	
	UNIT	rs 6 7 St	CALE COUNT DESCRIPTION	OF REVISIONS		DESIGNED		CHECKED	DATE
	mm	$, \mid \bigoplus \   \Box \mid ,$	2:1						
			APPROVED : HY. KOBAYASHI 18.	DRAWING NO.		EDC-117299-31-00			
	u	RELECTRIC	CHECKED : HY. KOBAYASHI 18.	)2. 26 PART		HR08D-12WLPK-10SCC31			`(31)
<b>∣</b> ⊿∏		CO. LTD.	DESIGNED : DS. MATSUNE 18.	)2. 24 NO.		111100	D IZWLIN 1030C312		,(31)
		CO., LID.	DRAWN : AI. NISHIYAMA 18.	በኅ ላር !	NO.	CL108	-0265	5-4-31	$\left  \triangle \right ^{1}$

FORM HC0011-5-7