



Feb.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demands high reliability, kindly contact our sales window correspondents.









PANEL CUTOUT
(t=1 to 3)

HRS DRAWING FOR REFERENCE

NOTES 1. APPLICABLE CRIMP CONTACT:HR22-PC-222(CL122-0009-0)
※APPLICABLE WIRE:AWG#24 TO 28, JACKET DIAMETER:φ1.15(MAX)
APPLICABLE CONTACT REMOVAL TOOL(EXTRACTION TOOL):RP6-SC-TP(CL150-0039-0)
2 THE RECOMMENDED CLAMP TORQUE, REF. NO. 5 : 2 TO 3N・m.
AND LOCTITE 243, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO
PREVENT FROM LOOSENING.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
3	Silicone rubber	(Black)			
2	Polybutylene terephthalate	(Black) UL94V-0	5	Brass	Nickel plating
1	Zinc alloy	Nickel plating	4	Brass	Nickel plating

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△0					

HIROSE ELECTRIC CO., LTD.

APPROVED	EJ. KUNII	16.02.13	DRAWING NO. EDC-042800-73-00
CHECKED	EJ. KUNII	16.02.13	PART NO. HR22-12WTRA-20PC(73)
DESIGNED	SJ. SHIMIZU	16.02.13	CODE NO. CL122-0005-0-73 △0 1/1
DRAWN	SJ. SHIMIZU	16.02.13	