

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	— °C TO — °C	STORAGE TEMPERATURE RANGE	— °C TO — °C	
	VOLTAGE	350 V AC , 490 V DC	OPERATING HUMIDITY RANGE	— % TO — %	
	CURRENT	—	APPLICABLE CABLE	—	
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	×	×
MARKING		CONFIRMED VISUALLY.		×	×
ELECTRIC CHARACTERISTICS					
INSULATION RESISTANCE		500 V DC.	5000 MΩ MIN.	×	×
VOLTAGE PROOF		1250 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	×	×
MECHANICAL CHARACTERISTICS					
VIBRATION		FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, AT 2h, FOR 3 DIRECTIONS.	1) NO ELECTRICAL DISCONTINUITY OF 10 μ s. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
SHOCK		490 m/s ² DIRECTION OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.		×	—
ENVIRONMENTAL CHARACTERISTICS					
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 25 → 85 → 25 °C. TIME 30 → 10~ 15 → 30 → 10~15 min UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
DAMP HEAT (STEADY STATE)		EXPOSED AT 40°C , 90~95 % , 96 h.	1) INSULATION RESISTANCE: 10 MΩ MIN (AT HIGH HUMIDITY). 1000 MΩ MIN (AT DRY). 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	×	—
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0					
REMARK			APPROVED	HO. MIWA	06. 07. 26
			CHECKED	HO. MIWA	06. 07. 26
			DESIGNED	YH. ENAMI	06. 07. 26
			DRAWN	YH. ENAMI	06. 07. 26
Unless otherwise specified, refer to JIS C 5402.					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-009409-01
HRS	SPECIFICATION SHEET		PART NO.	CDB-25P (05)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL211-0211-6-05	△ 1/1