

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4	
A						A	
B						B	
C						C	
D						D	
E						E	
F						F	

NOTE 1) A LOCK SCREW IS SUPPLIED TO ENTERING 100 PIECES TO THE QUANTITY 1 OF THE PRODUCT(CL211-5181-4-01).

2) THE APPLICABLE PANEL THICKNESS PUT BETWEEN THIS PRODUCT AND A CONNECTOR IS FROM 0.8 TO 1.2mm.

1	STEEL	OVER PLATING : NICKEL 2μm MIN UNDER PLATING : COPPER 1μm MIN	2	STEEL	OVER PLATING : NICKEL 2μm MIN UNDER PLATING : COPPER 3μm MIN		
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS		
UNITS mm		SCALE 5 : 1	COUNT 	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.		APPROVED : EJ. WAKATSUKI 13.12.09	DRAWING NO. EDC4-045777-01				
		CHECKED : EJ. WAKATSUKI 13.12.09	PART NO. RDG-LNA-W1<01>				
		DESIGNED : TS. ITO 13.12.06	CODE NO. CL211-5181-4-01				
		DRAWN : TS. ITO 13.12.06					

FORM HC0011-5-51