APPLICABLE STANDARD											
OPERATING TEMPERATURE RANGE			−25°C TO +85	ō°C	STORAGE TEMPERATURE RANG		−25°C TO +60°C				
RATING	OPERATING&STORAGE HUMIDTY RANGE		85%MAX		APPLICABLE CABLE			Δ CABLE DIAMETER: φ6.4~7			
	CL	JRRENT			VO	VOLTAGE					
					•						
SPECIFICATIONS											
	EM		TEST METHOD			F	REQUIREMENTS QT AT				
CONSTRUCTION GENERAL EXAMINATION VISUALLY AND BY			Y MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			X	Х	
MARKING		CONFIRMED VISUALLY.					5 5101			X	
WATCH									X	^	
COUN	T DE	SCRIPTION OF REVISIONS			DESIGNED			CHECKED	DA	\TE	
3 1		DIS-E-00014810			KIM JAEHYEON			KG. OKITA	2023	30928	
REMARK THIS PRODUCT SHALL BE MATED WITH DH3 * B-27S, IT APPLIE						APPROVE		AO. SUZUKI	2009050		
			ICAL, ENVIRONMENTAL			KED	KN. ICHIKAWA	2009	20090507		
	ACTERISTIC					DESIG	NED	MO. SHIMOYAMA	20090507		
Unless	to IEC 60512.		DRAWN			MO. SHIMOYAMA	MO. SHIMOYAMA 20090507				
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAV	WING NO.		ELC4-126627-00			
жs	LDC SPECIFICATION SHEET					D.	l.	DH-27-CT1B			
N	HIR	OSE ELECT	RIC CO., LTD.) CI	024	4-0030-2-00			