APPLICA	BLE STAN	DARD										
	OPERATING		−25°C TO +85°C		STORAGE TEMPERATURE RANGE		−25°C TO +60°C					
RATING	OPERATURE RANGE OPERATING&STORAGE HUMIDTY RANGE CURRENT		85%MAX	TEMPERATURE RAIN			<u> </u>	\triangle CABLE DIAMETER: ϕ 5.1~7.1				
						VOLTAGE						
	•				1			•				
			SPEC	IFICA	10ITA	NS						
	EM		TEST METHOD	DD				REQUIREMENTS QT AT				
	XAMINATION	VISUALLY AND B	SUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING. X X					
MARKING		CONFIRMED VISUALLY.				-					Х	
COUN	T DE	SCRIPTION OF REVISIONS			DESIGNED				CHECKED	DATE		
<u>↑ 2 DIS-E-00003216 KN. ICH</u> REMARK							APPRO	VED	TU. TANIGUCHI AO. SUZUKI	20201019		
THIS PRODUCT SHALL BE MATED WITH DH3 *								KED AH. KODAMA			20100407	
		ECHANICAL, ENV	HANICAL, ENVIRONMENTAL			DESIG		D MO. SHIMOYAMA 20		0407		
CHARACTERISTICS.							DRAWN		TM. ONO 2010		0407	
Unless otherwise specified, refer to IEC 60512. 🛆 Note QT:Qualification Test AT:Assurance Test X:Applicable Test						DRAWING NO.			ELC4-126852-13			
IDC T						PART NO.		DH-17-CT1B (13)				
	SPECIFICATION SHEET					NO.	CI	24/	I-0039-7-13	A	1/1	