APPLICA	BLE STAN	DARD									
OPERATING TEMPERATURE			_25°C TO ±95°C		STORAGE TEMPERATURE RA		−25°C TO +60°C				
RATING	VOLTA	AGE			APPLICA	BLE CABLE	Z	A CABLE DIAMETER: 4		~7.1	
	CURR	ENT									
					•		',				
SPECIFICATIONS											
	EM	TEST METHOD			REQUIREM			IREMENTS	QT	АТ	
CONSTRUCTION		T			1				Х		
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.				ACCORDING TO DRAWING.				X	
MARKING		CONFIRM	MED VISUALLY.					X	Х		
COUN	IT DE	SCRIPTION			DESIGNE	DESIGNED		CHECKED		DATE	
2 DEMARK		DIS-E-00003216			KN. ICHIKAV		TU. TANI GUCHI		20201019		
	REMARK THIS PRODUCT SHALL BE MATED WITH DH30B-17S, IT AP					APPRO		AO. SUZUKI	20100407		
TO DF	130B-17S AB	OUT A M		ANICAL, ENVIRONMENTAL			KED	AH. KODAMA	20100407		
	CTERISTICS		A				NED	MO. SHIMOYAMA	20100407		
Unless otherwise specified, refer to IEC 60512. 🛆					DRAW			TM. ONO 2010040		0407	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWING NO.			ELC4-126946-13			
RS		SPECIFICATION SHEET			PART NO.			DH-17-CT2B (13)			
ı -	HIR	OSE ELECTRIC CO., LTD.			CODE NO	o. CL	CL244-0047-5-13 🛆 1			1/1	