


May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.


A
B
C
D
E
F



Notes. 1. Recommended cable condition is shown below.
⚠ A list of compatible cables is available on the Hirose website.
When using a non-recommended cable, please contact a Hirose sales representative.
Refer to the technical specification (ETAD-E3213) for wiring and assembly procedures.


⚠ Recommended Cable

Items		Recommended Condition
Conductor	Size	AWG#24 to 25
	Composition	7 stranded
	Material	Annealed copper wire
Insulation O. D.		φ1.1~1.25mm
Braid Shield		Tin plating
Sheath O. D.		φ6.3~7.2mm



2. This product (Type B) is used for non Ethernet applications like signaling, serial or other industrial bus communication systems.
Please use Type A for 10/100 Mbit/s and 1/10 Gbit/s Ethernet communication.


⚠ Mating Key






⚠ 3 Excluding the plug unit, this product is packaged separately by the type of parts.
The shield shell is packaged prior to bending. (See next page.)
Refer to the technical specification (ETAP-E3224) for packing.

4	PA	Black, UL94V-0	9	PC	Dark gray, UL94V-0
3	Stainless Steel		8	PC	Dark gray, UL94V-0
2	PA	Dark gray, UL94V-0	7	Stainless Steel	Nickel 0.2 μm min
1	Copper Alloy	Contact area : Palladium-Nickel 0.75 μm min + Gold 0.05 μm min	6	Stainless Steel	Nickel 1 μm min
		Wiring area : Gold 0.03 μm min	5	PC	Clear yellow, UL94V-0
		Under plating : Nickel 2 μm min			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT 6	DESCRIPTION OF REVISIONS DIS-E-00006881	DESIGNED MT. YASUDA
HIROSE ELECTRIC CO., LTD.		APPROVED : MN. KENJO	20200519	DRAWING NO.	EDC-129982-01-00
		CHECKED : KI. NAGANUMA	20200519	PART NO.	IX31G-B-10S-CVL2(7.0)(01)
		DESIGNED : MT. YASUDA	20200519	CODE NO.	CL0251-0070-0-01
		DRAWN : MY. KOMUKAI	20200519		
					DATE 20211025

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



3 Product Structure



HRS	DRAWING NO.	EDC-129982-01-00
	PART NO.	IX31G-B-10S-CVL2<7.0>(01)
	CODE NO.	CL0251-0070-0-01
		1/2