


Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

[ASSEMBLE TOOL]
 APPLICABLE OUTER CONDUCTOR CRIMPING TOOL
 :HT303/UM.MSS-T-1(2.5 HOLE)



RECOMMENDED PANEL CUTOUT
 (PANEL THICKNESS : 1~2 mm)

RoHS COMPLIANT

5	PTFE		10	POLYOLEFIN	HEAT SHRINK TUBING(BLACK)
4	BERYLLIUM COPPER	GOLD PLATING	9	STEEL	NICKEL PLATING
3	BRASS	NICKEL PLATING	8	BRASS	NICKEL PLATING
2	PTFE		7	BRASS	NICKEL PLATING
1	BRASS	NICKEL PLATING	6	BRASS	NICKEL PLATING
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm	SCALE 2 : 1	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.			APPROVED : MH. YAMANE 11.01.24 CHECKED : TS. NOBE 11.01.21 DESIGNED : YI. FUNADA 11.01.18 DRAWN : YI. FUNADA 11.01.18	DRAWING NO. EDC4-131200-40 PART NO. BNC(75)-BPJ-1.5CV-(P)(40) CODE NO. CL302-0369-8-40		