

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

6.3 ± 0.3

7.3 ± 0.2

6 ± 0.2

6.29

24.29 ± 0.45

12 ± 0.2

0.52 ± 0.2

0.36 ± 0.05

4.0 ± 0.2

1/4-36UNS-2A

6

5

4

3

2 PRESS FITTING

1 PRESS FITTING

NOTE1. FOR THE USE OF THIS PRODUCT, PUSH IT ON MS-162

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	BERYLLIUM COPPER	GOLD	6	PTFE	
2	PHOSPHOR BRONZE	NICKEL	5	PTFE	
1	PHOSPHOR BRONZE	NICKEL	4	STAINLESS STEEL	PASSIVATE

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	<i>Y. Matsuo</i> '05. 8. 23	<i>Y. Matsuo</i> '05. 8. 23	<i>T. Gaki</i> '05. 8. 24	<i>K. Kamekura</i> '05. 8. 24	

DRAWING NO.	PART NO.
EDC4-180486	MS-162-HRMJ-1

UNITS	CODE NO.
mm	CL358-0210-5

HRS HIROSE ELECTRIC CO., LTD.

FORM NO. 228

RFD