



USER GUIDE for CX90M3-24P

Table of contents

1.	Revision History	-----	3
2.	Introduction		
2.1	Purpose	-----	3
2.2	Scope	-----	3
2.3	Reference Specification	-----	3
3.	Product Information		
3.1	Product Feature	-----	4
3.2	Specification	-----	4
3.3	Product Size	-----	5
3.4	Pin Assignment	-----	5
3.5	Manufacturing Date Code System	-----	6
3.6	Part List	-----	7
3.7	Configuration of Product Name	-----	7
3.8	Reel Dimensions	-----	8
3.9	Emboss Carrier Tape Dimensions	-----	8
3.10	Packing Quantity	-----	8
3.11	Peeling Strength	-----	8
3.12	Product Dimension	-----	9
4.	Notice for Soldering		
4.1	Recommended Reflow Temperature Profile	-----	10
4.2	PCB Designing	-----	11
4.3	PIP (Place In Paste)	-----	11
4.4	Metal Mask Designing	-----	12
4.5	Solder Paste	-----	12
5	Notice for Connector Handling		
5.1	Mating plug	-----	13

1. Revision History

Revision History	Date	Handled by	Remarks
1.0	January 30, 2023	Y.J.KIM	Initial release

2. Introduction

2.1 Purpose

The guidelines are intended to provide information on product features and how to handle them.

Guidelines are intended to provide general information and do not limit your design or guarantee results in all situations.

2.2 Scope

Guidelines describe basic design information, recommended device dimensions, and regulatory requirements.

These guidelines will be revised from time to time to reflect changes in technology and production capacity.

2.3 Reference Specification

- Universal Serial Bus Type-C Cable and Connector Specification

Revision 2.1 May 2021

3. Product Information

3.1 Product Feature

- 1) Compliant to USB Type-C specification
- 2) 5A current rating for quick charging.
- 3) Improved peeling strength using 4 THR* mounting posts.
* Through-Hole-Reflow
- 4) Reversible plug orientation ensures easy insertion.
- 5) USB4 Gen.2 transmission speed
- 6) Clear tactile click due to superior lock Design
* When using 2 HRS products



3.2 Specification

No. of Contacts	24
P.C.B Mounting type	Mid-Mount
Soldering type	Double row SMT
Current rating	DC 1.25A Max. for each power pin (i.e. A1, A4, A9, A12, B1, B4, B5, B9, B12) DC 0.25 A for the other pins
Voltage rating	48V AC/DC
Operating Temperature	-40°C ~ +105°C (Including Temp.rise), 95% RH MAX
Storage Condition	-10°C ~ +60°C (With Packing), 15% ~ 70% RH
Contact Resistance	40mΩ Max. (Initial)
Withstanding Voltage	100V AC for 1 minute
Insulation Resistance	100MΩ Min. (500V DC)
Mating Cycles	10,000 times
Insertion/ Extraction Force	Insertion: 5~20N, Extraction: 8~20N (Initial), 6~20N (After test)

Note


- * Storage conditions apply to original packaging only, void if opened. Warranty period is 12month max. in the storage conditions above and calculated by manufacture date

3.3 Product Size





Width	12.00
Length	7.85
Height	3.16
Center Height	0.52

3.4 Pin Assignment




A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
GND	TX1+	TX1-	Vbus	CC1	D+	D-	SBU1	Vbus	RX2-	RX2+	GND
GND	RX1+	RX1-	Vbus	SBU2	D-	D+	CC2	Vbus	TX2-	TX2+	GND
B12	B11	B10	B9	B8	B7	B6	B5	B4	B3	B2	B1



Detail A

Detail B





3.5 Manufacturing Date Code System



Year		Month		Day		Production Line	
Ex.	Mark	Ex.	Mark	Ex.	Mark	Ex.	Mark
2020	0	Jan.	1	1st	01	SAMPLE	S
2021	1	Feb.	2	2nd	02	Manual #1	1
2022	2	Mar.	3	3rd	03	Manual #2	2
2023	3	Apr.	4	4th	04	Manual #3	3
2024	4	May	5	5th	05	Manual #4	4
2025	5	Jun.	6	6th	06	...	...
2026	6	Jul.	7	7th	07	Auto #1	A
2027	7	Aug.	8	8th	08	Auto #2	B
2028	8	Sep.	9	9th	09	Auto #3	C
2029	9	Oct.	A	10th	10	Auto #4	D
2030	0	Nov.	B	11th	11	Auto #5	E
...	...	Dec.	C	...	...	...	...

3.6 Part List

No	Part	Materials	Finish / Color
1	Insert case	Thermoplastic	UL94V-0, Black Color
2	Contact 1st	Copper Alloy	Contact Area : Gold over Nickel Solder Area : Gold over Nickel
3	Contact 2nd	Copper Alloy	Contact Area : Gold over Nickel Solder Area : Gold over Nickel
4	Mid plate	Stainless Steel	Contact Area : Gold over Nickel The Other Area : Nickel plating
5	Main Shell	Stainless Steel	Nickel plating




3.7 Configuration of Product Name


CX 90 M 3 - 24 P
 (1) (2) (3) (4) (5) (6)

①	Series Name	CX	CX Series
②	Soldering Type	90	Right angle SMT
③	Mounting Type	M	Mid-Mount
④	Serial No	3	None or 1,2,3...
⑤	Contact No	24	24 position
⑥	Contact Type	P	Male contact

3.8 Reel Dimensions



3.9 Emboss Carrier Tape Dimensions



※ Emboss Tape was designed in accordance with EIA-481


3.10 Packing Quantity Per Reel : 1,500 PCS

3.11 Peeling Strength:

Cover tape shall have a total peel strength of from 0.1N to 1.3N

4. Notice for Soldering

4.1 Recommended Reflow Temperature Profile




- Profile measuring point
The temperature profile indicates the board surface temperature at the point of contacts with the connector terminals.
- Reflow cycles
Up to 2 cycles of reflow soldering are possible under the same
* Temperature between 1st and 2nd reflow must be cooled down to room temperature
- Reflow heating method and condition
Far-infrared heater and hot convective blowers used in combination,
normal atmosphere, or nitrogen atmosphere..
- Top surface of the contact leads may not covered by solder depending on reflow condition

4.2 PCB Designing


RECOMMENDED PCB LAYOUT (TOP-VIEW)

(REFERENCE ONLY)




4.3 PCB Thickness

Recommended PCB thickness is 0.80 ± 0.05 mm considering 0.6 ± 0.1 mm of PIP leg length.



Section A-A



The PIP leg can be protruded to the bottom side of PCB in case the PCB thickness is less than the PIP leg length.

5. Notice for Connector Handling

5.1 Mating Plug

Please use USB Type-C Plug only

