Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .



PARTS NO.	HRS NO.	CONTACTS	A	B	C
DF13-10DS-1.25C	CL536-0550-2	10	10.4	8.0	5.0
DF13-20DS-1.25C	CL536-0555-6	20	16.65	14.25	11.25
DF13-30DS-1.25C	CL536-0560-6	30	22.9	20.5	17.5
DF13-40DS-1.25C	CL536-0565-0	40	29.15	26.75	23.75





HRS DRAWING FOR REFERENCE

2 FIG. A





CONTACT NO. 1

ON EVERY FIVE CONTACTS

NOTES 1 100 CONNECTORS ARE IN ONE PACK
2 LANCE CONFIGURATION, 30 AND 40 CONTACTS SHALL BE FIG. A.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
			1	POLYAMIDE	(BEIGE) UL94V-0

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	H. IGARASHI 95 3 14	H. Igarashi 95. 3. 15	M. Nakamura 95.3.16	M. Yamano 95.3.16	

SCALE	DRAWING NO.	PART NO.
5 : 1	EDC3-160109-02	DF13-*DS-1.25C
UNITS mm	HRS HIROSE ELECTRIC CO., LTD.	CODE NO. CODE NO. SHALL BE IN ACCORDANCE WITH TABLE

1/1

FORM No. 229 INC

TO