Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





CODE No.	CONTACT	A	B	C	D	E
CL537-0396-0-51	10	4.7	2.0	2.8	3.2	2.8
CL537-0397-0-51	14	5.7	3.0	3.8	4.2	3.8
CL537-0398-0-51	20	7.2	4.5	5.3	5.7	5.3
CL537-0399-0-51	30	9.7	7.0	7.8	8.2	7.8
CL537-0487-0-51	32	10.2	7.5	8.3	8.7	8.3
CL537-0488-0-51	36	11.2	8.5	9.3	9.7	9.3
CL537-0489-0-51	40	12.2	9.5	10.3	10.7	10.3
CL537-0490-0-51	50	14.7	12.0	12.8	13.2	12.8
CL537-0491-0-51	60	17.2	14.5	15.3	15.7	15.3
CL537-0492-0-51	80	22.2	19.5	20.3	20.7	20.3





HRS DRAWING FOR REFERENCE

RECOMMEND METAL MASK PATTERN (10:1)



METAL MASK THICKNESS : 120 μm

RECOMMENDED LAND PATTERN (10:1)







NOTES 1 LEAD CO-PLANARITY SHALL BE 0.08 mm MAX.
2 IF THERE IS PATTERN ON ▨ PART, THERE IS A POSSIBILITY THAT IT WILL MAKE CONTACT WITH THE LEADS.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATED 0.2μm min LEAD AREA:GOLD PLATED 0.015μm min OTHERS(UNDER PLATING):NICKEL PLATED 2μm min	6	PS	CLEAR (REINFORCEMENT COLLAR)
			5	PS	BLACK (PLASTIC REEL)
			4	POLYESTER	CLEAR (COVER TAPE)
1	POLYAMIDE	UL94V-0, BLACK	3	PS	CLEAR (EMBOSSED CARRIER TAPE)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	5 : 1	△0	0				

HIROSE ELECTRIC CO., LTD.

APPROVED	WR. FUKUCHI	20200702	DRAWING NO. EDC-390687-51-77
CHECED	TS. MIYAZAKI	20200702	PART NO. DF12NC(3.0)-*DP-0.5V(51)
DESIGNED	RN. IIDA	20200702	CODE NO. CL537
DRAWN	RN. IIDA	20200702	△0 1/2

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





CODE No.	CONTACT	G	H	J	K	L	M
CL537-0396-0-51	10	16	-	7.5	0.30	17.5	6.4
CL537-0397-0-51	14	16	-	7.5	0.30	17.5	7.4
CL537-0398-0-51	20	16	-	7.5	0.38	17.5	9
CL537-0399-0-51	30	24	-	11.5	0.38	25.5	11.5
CL537-0487-0-51	32	24	-	11.5	0.30	25.5	12
CL537-0488-0-51	36	24	-	11.5	0.38	25.5	12.6
CL537-0489-0-51	40	24	-	11.5	0.38	25.5	14
CL537-0490-0-51	50	24	-	11.5	0.38	25.5	16.4
CL537-0491-0-51	60	32	28.4	14.2	0.38	33.5	18.6
CL537-0492-0-51	80	44	40.4	20.2	0.38	45.5	23.8



Q—Q(FREE)



STYLE AND DIMENSION OF REEL (FREE)



NOTES 3 1 REEL 1000 CONNECTORS.

4 AT THE BEGINNING OF THE REEL, 30 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 20 COMPONENTS SHALL BE EMPTY.

5 WHEN THE TAPE WIDTH IS 32 mm OR 44 mm, SPROCKET HOLES SHALL BE SET ON BOTH SIDE OF REEL AS SHOWN ON THIS DRAWING.

6 PEEL FORCE REFERS TO JIS C 0806, AND IEC 60286-3.

7 AFTER PACKING, ROLL 2 METERS OF THE REINFORCEMENT COLLAR TO OUTER CIRCUMFERENCE OF TAPE AND REEL POCKET, AND TAPE DOWN AT THE END THE COLLAR.

HRS DRAWING FOR REFERENCE

HRS	DRAWING NO.	EDC-390687-51-77
	PART NO.	DF12NC(3.0)-*DP-0.5V(51)
	CODE NO.	CL537