© 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE



RECOMMENDED LAND PATTERN DIMENSION OF PCB



3 FLOATING RANGE









PCB DISTANCE(No scale)





CROSS SECTION OF MATING
(No scale)



2 DRAWING FOR PACKING(No scale)





B (10 : 1)



A (1 : 1)



1 Lead CO-Planarity is 0.1mm MAX.
2 This is packaged in tray. (60pcs/tray)
3 Floating range of this connector is ±0.8mm MAX in the X direction and ±0.6mm MAX in the Y direction.
4 Blemish and hit mark can be occured through out the manufacturing process which doesn't affect quality level.
5 It shows the vacuum pickup area. Remove the mylar tape before mating connectors.
6 Please note that excessive wrenching force could damage this connector.
Please refer to the guideline for detailed regulations of the mating method.
7 The dimensions in parentheses are for references.
8 Please use the connectors within the specified PCB distance.

NO.	MATERIAL	FINISH , REMARKS
6	POLYIMIDE	(TAPE FOR VACUUM PICKUP)
5	POLYSTYRENE	(TRAY)
4	BRASS	TIN-PLATING 1μm
3	COPPER ALLOY	CONTACT AREA:GOLD 0.1μm LEAD AREA:GOLD 0.03μm UNDER PLATING:NICKEL 1μm
2	POLYAMIDE	BLACK UL94V-0
1	POLYAMIDE	BLACK UL94V-0

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1					

HIROSE ELECTRIC CO., LTD.

APPROVED	HS. OKAWA	14.06.09
CHECKED	KN. SHIBUYA	14.06.09
DESIGNED	TS. OONO	14.06.09
DRAWN	TS. OONO	14.06.09

DRAWING NO.	EDC3-336328-01
PART NO.	FX20-100P-0.5SV20(10)
CODE NO.	CL570-1010-1-10

△ 1/1