



1 2 3 4 5 6 7 8


COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE

A B C D E F



RECOMMEND PC BOARD HOLE PATTERN (MOUNTING SIDE)

MATING SIDE



PART No.	CODE No.	A	B	C	D
FX2B-20PA-1.27DS(71)	CL572-0721-7-71	20	30.33	11.43	18.05
FX2B-32PA-1.27DS(71)	CL572-0722-0-71	32	37.95	19.05	25.67
FX2B-40PA-1.27DS(71)	CL572-0723-2-71	40	43.03	24.13	30.75
FX2B-52PA-1.27DS(71)	CL572-0724-5-71	52	50.65	31.75	38.37
FX2B-60PA-1.27DS(71)	CL572-0725-8-71	60	55.73	36.83	43.45
FX2B-68PA-1.27DS(71)	CL572-0726-0-71	68	60.81	41.91	48.53
FX2B-80PA-1.27DS(71)	CL572-0727-3-71	80	68.43	49.53	56.15
FX2B-100PA-1.27DS(71)	CL572-0728-6-71	100	81.13	62.23	68.85

NOTES
1 STANDOFF DIFFERS ACCORDING TO PRODUCTS.
2 NUMBER OF PIN.
3. THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

D (INDICATIONS)

1, 2 POLYAMIDE	BLACK	UL94V-0	3~6	BRASS	CONTACT AREA: GOLD FLASH
NO.	MATERIAL	FINISH,	REMARKS	NO.	MATERIAL
CODE NO. (OLD)	CL				
SCALE	FREE				
UNITS	mm				
DRAWING NO.	EDC3-153963-21				
PART NO.	FX2B-**PA-1.27DS(71)				
DESIGNED	I. OKAYAMA	CHECKED	H. OKAWA	APPROVED	H. OKAWA
DATE	04.06.02	DATE	04.06.02	DATE	04.06.14
CL					
CODE NO.					
CL572					
FORM NO. 233					