






Jan.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD						
Rating	Operating Temperature Range	-40 °C to 140 °C ⁽¹⁾	Storage Temperature Range	-10 °C to 60 °C ⁽²⁾		
	Voltage	125 V AC ⁽³⁾	Storage Humidity Range	Relative humidity 60% max (Not dewed)		
	Current	0.5 A	Operating Humidity Range	Relative humidity 85% max (Not dewed)		
SPECIFICATIONS						
ITEM	TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION						
General Examination	Examined visually and with a measuring instrument.		According to the drawing.		x	x
Marking	Confirmed visually.				x	x
ELECTRICAL CHARACTERISTICS						
Contact Resistance	Measured at 100 mA MAX.(DC or 1000Hz)		65mΩ MAX.		x	-
Insulation Resistance	Measured at 250 V DC.		1000 MΩ MIN.		x	-
Voltage Proof	375 V AC applied for 1 min.		No flashover or breakdown.		x	-
MECHANICAL CHARACTERISTICS						
Mating and Unmating Forces	Measured with an applicable connector.		Mating Force: 60 N MAX. Unmating Force: 6.6 N MIN.		x	-
Mechanical Operation	Mated and unmated 10 times.		①Contact Resistance : 75mΩ MAX. ②No damage, cracks or looseness of parts.		x	-
Vibration	Frequency 50~100 → 100~150 → 150~300Hz Acceleration 98 → 98~294 → 294 m/s ² 1 cycle 3 min 3 h for 3 axial directions ⁽⁴⁾		①No electrical discontinuity of more than 1 μs. ②No damage, cracks or looseness of parts.		x	-
Shock	Acceleration 980 m/s ² , duration of pulse 6 ms at 3 times for 3 axial directions.				x	-
ENVIRONMENTAL CHARACTERISTICS						
Damp Heat (Steady state)	Exposed at 60±2 °C, 90 ~ 95 %, 1000 h.		①Contact Resistance : 75mΩ MAX. ②Insulation Resistance : 1000 MΩ MIN. 		x	-
Rapid Change of Temperature	Temperature -40 → +140 °C Time 30 → 30 min. under 1000 cycles. (Relocation time to chamber : within 2~3 MIN)		③No damage, cracks or looseness of parts.		x	-
Cold	Exposed at -40°C, 1000 h		①Contact Resistance : 75mΩ MAX.		x	-
Dry Heat	Exposed at 140°C, 1000 h		②No damage, cracks or looseness of parts.		x	-
Sulfur Dioxide	Exposed at 40±2°C, 80±5%RH, 25±5 PPM for 96 h.		Contact Resistance : 75mΩ MAX.		x	-
Resistance to Soldering Heat	1)Reflow soldering : Peak TMP : 260°C MAX Reflow TMP: 220°C MIN for 60sec 		No deformation of case of excessive looseness of the terminal.		x	-
Solderability	Soldered at solder temperature 240±3°C for immersion duration, 3 sec.		A new uniform coating of solder shall cover a minimum of 95 % of the surface being immersed.		x	-
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
	1	DIS-F-00016361	TK. ABE	HH. SHINDO	20221215	
Notes	⁽¹⁾ Include temperature rise caused by current-carrying. ⁽²⁾ "STORAGE" means a long-term storage state for the unused product before assembly to PCB. ⁽³⁾ The creepage distance conforms to IEC 60664-1. Voltage effective value: 32V AC, Pollution Degree: 2 ⁽⁴⁾ Amplitude between connector mounting part and PCB is 0.05mm MAX.			APPROVED	HH. SHINDO	20190719
				CHECKED	KN. SHIBUYA	20190718
				DESIGNED	TK. ABE	20190718
				DRAWN	TK. ABE	20190718
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC-387245-00-00		
	SPECIFICATION SHEET		PART NO.	FX26-60P-1SV5		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL0576-1506-0-00		1/1