Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





Fig.1 Recommended spacer height (Free)



Fig.2 Mating cross section (Free)

HRS DRAWING FOR REFERENCE

Table.1 Stacking height and connector combinations 1

Board distance (Stacking height)	Header connector of Board α	Interposer	Header connector of Board β	Recommended spacer height(L) 3
11mm	FX10A-144P-SV1(**)	FX10-144IP-8PH(03)	FX10A-144P-SV2(**)	11±0.127mm
12mm	FX10A-144P-SV1(**)		FX10A-144P-SV3(**)	12±0.127mm
13mm	FX10A-144P-SV1(**)		FX10A-144P-SV4(**)	13±0.127mm

Table.2 Pin configuration of Interposer 4

Row A Pin No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72
Pin configuration	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S
Row B Pin No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72
Pin configuration	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S	S

S: Signal

Note. 1 The header connectors are decided by board distance (stacking height). Connector combination is shown in Table 1.
2 Fixed side (Black side) of interposer should be mated with header mounted on board α.
Mating side (Gray side) should be mated with header mounted on board β.
3 Spacers are required to support the PWB's and protect the SMT solder joints.
Recommended spacer height is shown in Table 1.
4 Pin configuration is shown in Table 2.
This product consists of 144 Single-ended lines.
5 Lot No. shall be marked on the indicated position.
6 50pcs of this product are packed in soft tray. See Fig.3 for details.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
2	LCP(Black)	UL94V-0	4	PS	(Tray)
1	LCP(Gray)	UL94V-0	3	Copper Alloy	Ni1.5μm+Au0.76μm

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	0				

HIROSE ELECTRIC CO., LTD.

APPROVED	TM. MATSUO	17. 07. 24	DRAWING NO. EDC-361672-03-00
CHECKED	TM. MATSUO	17. 07. 24	PART NO. FX10-144IP-8PH(03)
DESIGNED	AS. MATSUZAWA	17. 07. 24	
DRAWN	XINGYU CHENG	17. 07. 24	CODE NO. CL608-0012-0-03

0 1/2

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS DRAWING FOR REFERENCE

Fig.3 Drawing for packing (1:2) <6>



Fig.4 Stacked tray drawing (1:2)

HRS	DRAWING NO.	EDC-361672-03-00
	PART NO.	FX10-144IP-8PH(03)
	CODE NO.	CL608-0012-0-03 △0 2/2