

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.







Fig.1(FREE)



Mating Cross Section (Free)

- NOTE.
- 1 Mounting side is mated with the receptacle:IT3M-200S-BGA(**) and fixed with the latch.
 - 2 Lot No. shall be marked on the indicated position.
 - 3 The indicated mother board and daughter card shall be fastened to the additional reinforcements to prevent the stress on IT3*-200S-BGA(**) solder joints.
 - 4. Please refer to HIROSE document: ETAD-F0347 'IT3 design guideline'.
 - 5. This product consists of 200 signal lines and 180 ground lines.
 - 6. 40pcs of this products are packed in a soft tray.
 - 7. Standard package of 80pcs are packaged in a carton box.

NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
3	LCP	BLACK	UL94V-0	5	Copper Alloy		CONTACT AREA:NICKEL(1.5µm)+GOLD(0.76µm)
2	PBT	GRAY	UL94V-0	4	Copper Alloy		CONTACT AREA:NICKEL(1.5µm)+GOLD(0.76µm)
1	PBT	BLACK	UL94V-0				

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△				
APPROVED : MK. EZAKI			15.08.26	DRAWING NO. EDC-157066-04-00		
CHECKED : MK. EZAKI			15.08.26	PART NO. IT3-200P-26H(04)		
DESIGNED : TF. SUGAWARA			15.08.26	CODE NO. CL636-0110-8-04		
DRAWN : KT. AIZAWA			15.08.26			