









RECOMMENDED CABLE SUBASSEMBLY



CABLE TERMINATION FIGURE(FREE)




- NOTES 1. APPLICABLE CABLE: THIN COAXIAL CABLE (AWG#42~AWG#46)
2. THIS CONNECTOR IS NOT HOT PLUG CABLE. MATE AND UNMATE WHILE THE POWER IS OFF.
3. THE ASSEMBLY IS COMPLETED BY COMBINING TWO PARTS (CONNECTOR UNIT, AND METAL SHIELDING). REFER TO THE TABLE FOR EACH ITEM No., PART NAME, PART No. AND CODE No.

ITEM No.	PART NAME	PART No.	CODE No.
1, 2	CONNECTOR UNIT	DF36-40P-0.4SD(55)	CL662-4002-3-55
-	METAL SHIELDING	DF36A-40P-SHL	CL662-4013-0-00

4. BLACK MARKS MAY OCCASIONALLY OCCUR IN MOLD RESIN, YET THEY DO NOT AFFECT CONNECTOR QUALITY.

			5		PS	BLACK		
			4		POLYESTER	CLEAR		
			3		PS	CLEAR		
1	PHOSPHOR BRONZE	CONTACT AREA : GOLD PLATING 0.1μm min TERMINATION AREA : GOLD PLATING 0.1μm min UNDER PLATING : NICKEL PLATING 1μm min		2	LCP	UL94V-0. BEIGE		
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS		
UNITS mm		SCALE 5 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.		APPROVED : MH. YAMANE		14. 07. 18	DRAWING NO.	EDC3-309125-03		
		CHECED : MH. TSUCHIDA		14. 07. 17	PART NO.	DF36-40P-0.4SD(55)		
		DESIGNED : AH. MIYAZAKI		14. 07. 16	CODE NO.	CL662-4002-3-55		
		DRAWN : AH. MIYAZAKI		14. 07. 16		 1/		

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS	DRAWING NO.	EDC3-309125-03		
	PART NO.	DF36-40P-0.4SD(55)		
	CODE NO.	CL662-4002-3-55	2	2