










- Notes 1. Per tray : 96 Pieces.
2. UL(File No. E52653)
C-UL(File No. E52653)
TUV (Certificate No. R50244085) authorization article.





Lot No. is displayed in one of the two locations.

Recommended PCB Layout
(Board thickness: $t=1.6 \pm 0.1\text{mm}$)



Packing Diagram (FREE)
340 ± 1



1	PBT	Black, UL94-V0	3	PS	Clear
NO.	MATERIAL	FINISH . REMARKS	NO.	Copper alloy	Contact Area : Au Plating 0.2μm min Lead Area : Tin Plating 1μm min Under Plating : Ni Plating 1μm min
UNITS mm		SCALE 2 : 1	COUNT 3	DESCRIPTION OF REVISIONS DIS-H-00011936	DESIGNED TS. MIYAKI
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA 20151128	DRAWING NO. EDC-338974-27-00		
		CHECKED : TS. FUKUSHIMA 20151128	PART NO. DF60-2P-10.16DSA(27)		
		DESIGNED : TS. KUMAZAWA 20151128	CODE NO. CL0680-3005-8-27		
		DRAWN : TS. KUMAZAWA 20151128	DATE 20220125		