


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.





Recommended PCB Layout
(Board thickens : t=1.6±0.1mm)




Aprication Diagram(1:1)










A(FREE)







Packaging Diagram (FRRE)



HRS DRAWING FOR REFERENCE

Notes 1. Per tray : 64 Pieces.
2. Refer to the technical specification (ETAP-H0816-00) for the packing type.
3. UL(File No. E52653)
C-UL(File No. E52653)
TUV (Certificate No. R50400864) authorization article.

4 4 Lot No. is displayed in one of the two locations.

NO.	MATERIAL	FINISH , REMARKS
1	PBT	Red, 94-V0
2	Copper Alloy	Contact Area : Au Plating 0.2μm min LEAD Area : Tin Plating 1μm min Under Plating : Ni Plating 1μm min
3	PS	White

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	4	3	DIS-H-00012301	TS. MIYAKI	SZ. ONO	20220217

APPROVED	HS. OKAWA	20171011	DRAWING NO. EDC-379290-50-00
CHECED	ST. WADA	20171011	PART NO. DF60FR-3P-10.16DSA(50)
DESIGNED	TT. OHSAKO	20171011	CODE NO. CL0680-4004-0-50
DRAWN	TT. OHSAKO	20171011	4 1/1

HIROSE ELECTRIC CO., LTD.