



Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.




RECOMMENDED PANEL CUT OUT DIMENSION











HRS DRAWING FOR REFERENCE

MATING FIGURE(1:1)





NOTE1. Per Pack : 100 Pieces
△3 2. Refer to the technical specification (ETAP-H1021-00) for the packing type.
3. UL(File No.E52653)
C-UL(File No.E52653)
TUV(Certificate No. R50400864)authorization article.

NO.	MATERIAL	FINISH , REMARKS
1	PBT	RED, UL94V-0

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△3	1	DIS-H-00004358	YK.YAMAGUCHI	ST.WADA	20181029

HIROSE ELECTRIC CO., LTD.

APPROVED	HS.OKAWA	20171011
CHECED	ST.WADA	20171011
DESIGNED	TT.OHSAKO	20171011
DRAWN	TT.OHSAKO	20171011


DRAWING NO.	EDC-379292-00-00
PART NO.	DF60FR-3EP-10.16C
CODE NO.	CL680-4006-0-00

△3 1/2


Mar.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

DF60F IN-LINE TYPE RECOMMENDED PANEL MOUNTING MANUAL (WHEN NUTS USES)


NUT INSTALLATION PROCESS



1. SLIDE A NUT (SIZE:M3) TO NUT FIX PART.




2. PRESS DOWN THE NUT UNTIL IT CLICKS,
   THEN THIS SOUND MEANS THE NUT HAS INSERTED
   INTO NUT HOLDER.




HRS DRAWING FOR REFERENCE

PANEL MOUNTING PROCESS

1. INSERT CONNECTOR INTO PANEL CUT OUT PART.



2. TIGHTEN A SCREW (SIZE:M3) TO FIX WITH PANEL.
   RECOMMENDED TORQUE : LESS THAN 0.49N・m



HRS	DRAWING NO.	EDC-379292-00-00
	PART NO.	DF60FR-3EP-10.16C
	CODE NO.	CL680-4006-0-00

△3 2/2