


NOTES) 1. ALL LEADS AND REINFORCED METAL FITTINGS CO-PLANARITY SHALL BE 0.1MAX.
 2.  IS NO PATTERN AREA OTHER THAN THE SAME CIRCUIT.
 3. HRS MARK AND CAV NO. ARE LOCATED IN APPROXIMAL AREA.
 4. GATE POSITIONS IS LOCATED IN APPROXIMAL AREA.
 A PART OF THE WALL MAY BE NOTCHED FOR SETTING GATE.

			7	PS	CLEAR, REINFORCEMENT COLLAR	
			6	PS	BLACK, PLASTIC REEL	
2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1#m MIN SMT LEAD:GOLD 0.05#m MIN UNDERPLATING:NICKEL 1#m MIN	5	POLYESTER	CLEAR, COVER TAPE	
			4	PS	CLEAR, EMBOSSED CARRIER TAPE	
			3	PHOSPHOR BRONZE	SURFACE:GOLD 0.05#m MIN UNDERPLATING:NICKEL 1#m MIN	
1	LCP	UL94V-0, BLACK				
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS	

UNITS mm		SCALE 10 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
HIROSE ELECTRIC CO., LTD.		APPROVED	• WR. FUKUCHI	20200220	DRAWING NO.	EDC-354974-75-02			
		CHECED	• TS. MIYAZAKI	20200220	PART NO.	DF40B(2.0)-20DS-0.4V(75)			
		DESIGNED	• RH. KAGAMI	20200220	CODE NO.	CL684-4213-6-75			
		DRAWN	• RH. KAGAMI	20200220					

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

