May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.







HRS DRAWING FOR REFERENCE

Note 1 FO cable and MT ferrule are NOT included in this product.
2. Use specifide tool to assemble this product.

NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
7	Zinc alloy die casting	Ni plating	14	Elastomer	Black
6	Stainless steel	———	13	Zinc alloy die casting	Ni plating
5	Zinc alloy die casting	Ni plating	12	PA	White
4	Stainless steel	For 24 fibers:Spring force 2kgf(Chrome)	11	Silicon rubber	Black
3	Silicon rubber	Red	10	Brass	Ni plating
2	Zinc alloy die casting	Ni plating	9	Brass	Ni plating
1	Zinc alloy die casting	Ni plating	8	Silicon rubber	Red

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	0					

HIROSE ELECTRIC CO., LTD.

APPROVED	YY. HIYAMA	20190603	DRAWING NO. EDC-385327-00-00
CHECKED	TS. YAMAZAKI	20190603	PART NO. MF11BMT-WP4CB02
DESIGNED	TY. SATO	20190603	CODE NO. CL709-7052-0-00
DRAWN	TY. SATO	20190603	0 1/1