






May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



ELV, RoHS COMPLIANT



MATED CONNECTORS



RECOMMENDED PCB PATTERN



NOTE 1. RECOMMENDED TEMPERATURE PROFILE FOR REFLOW
(REFER TO RIGHT FIG.)
USED REFLOW SYSTEM


NO. OF CYCLES : 2 MAX
PEAK : 250°C
OVER 230°C : 20~40s
PREHEAT : 150~180°C
90~120s Δ

2. TEMPERATURE FOR SOLDERING IRON
: 280~300°C WITHIN 2s

3. CO-PLANARITY SHALL BE 0.1mm MAX.

4. RECOMMENDED PCB THICKNESS IS 1.6mm.

5. RECOMMENDED SOLDER THICKNESS IS 0.15mm.





2	BRASS	SURFACE PLATING : TIN PLATING 1μm min	5	POLYESTER	
		UNDER PLATING : NICKEL 1μm min	4	POLYSTYRENE	
1	PA	BLACK UL94V-0	3	BRASS	SURFACE PLATING : TIN PLATING 1μm min
NO. MATERIAL		FINISH , REMARKS	NO. MATERIAL		FINISH , REMARKS
UNITS mm		SCALE 2 : 1	COUNT 4		DESCRIPTION OF REVISIONS DIS-T-00003979
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : HK. UMEHARA	20180906	DRAWING NO. EDC-383982-00-00	
		CHECKED : HH. TSUKUMO	20180906	PART NO. ZE05H-5P-2H	
		DESIGNED : YH. MAMADA	20180905	CODE NO. CL752-2120-0-00	
		DRAWN : MN. SATOH	20180905		
		DESIGNED	YONGMUN LEE	CHECKED	HH. TSUKUMO
		DATE	20181119		

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

PACKING STYLE


REEL DIMENSION (FREE)

PACKING STYLE DRAWING



CARDBOARD DIMENSION (FREE)

W=(405) (mm)
D=(405) (mm)
H= (51) (mm)



ASSEMBLY DRAWING	HRS	DRAWING NO.	EDC-383982-00-00	
		PART NO.	ZE05H-5P-2H	
		CODE NO.	CL752-2120-0-00	122