Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE

Mating guide (△ mark)

4 Fig.1
(1:1)

Oblique drawing
(1:1)













A-A



Notes
1 Applicable crimping contact:JRC-PC-112 (CL114-0239-6)
2 Applicable crimp contact extraction tool:HR41A-TP (CL150-0405-7)
3 Rotation examples are shown for Ref. No. ①, ③ and ⑥.
4 Fig.1 shows the appearance after assembly.
5 The cable pull and twisting strength and other characteristics may differ, depending on the cable structure, please confirm before the use.
6 The assembly of this product applies to the manual ETAD-C0312.

NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
3	PBT	(Black)	6	PBT	(Black)
2	Silicone rubber	(Red)	5	Polyamide	(White)
1	PBT	(Black)	4	Silicone rubber	(Red)

UNITS	SCALE		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	△1	1	DIS-C-00011650	SH. KOYAMA	EJ. KUNII	20220621

HIROSE ELECTRIC CO., LTD.

APPROVED	TP. KOMATSU	20220301
CHECED	EJ. KUNII	20220301
DESIGNED	SH. KOYAMA	20220228
DRAWN	SH. KOYAMA	20220228

DRAWING NO.	EDC-118142-81-00
PART NO.	HR41A-17WBJ-5PC(81)
CODE NO.	CL0141-0202-9-81 △1 1/1