

1				2				3				4							
△数 COUNT		訂正事項 DESCRIPTION OF REVISIONS		擔當 B Y		檢圖 CHKD		年月日 DATE		△数 COUNT		訂正事項 DESCRIPTION OF REVISIONS		擔當 B Y		檢圖 CHKD		年月日 DATE	
△								.		△								.	
△								.		△								.	
△								.		△								.	

Technical drawing of a cable assembly. The main view shows a cable with a length of 100 ± 4 mm. Callout 1 points to the connector housing, and callout 2 points to the cable jacket. A detail view shows a cross-section of the cable with a $\pm 45^\circ$ MAX angle. Another detail view shows the connector housing with dimensions 21 ± 0.2 and 0.9 ± 0.2 . A section view shows the cable jacket with a thickness of 0.81 mm. A note indicates the cable jacket thickness is $\phi 0.81$ mm. A diagram shows the cable assembly with a plug and a release tab, with a note indicating the cable is rated for $2N$ or less.

◆コネクタが嵌合された後、ケーブルに許容される負荷。
下記図は、ケーブルの最大許容荷重を示しています。
ケーブルにこの値を超える荷重を加えないでください。

プラグ
ケーブル
2N 以下
X
X
レセブタクル

コネクタ寸法図

21 ± 0.2
0.9 ± 0.2
(3.3)

[嵌合状態]

12 MAX
K.FL2-LP-040
K.FL2-R-SMT-1

1	K.FL2-LP-040	CL6345-****	2	φ0.81 ケーブル(シロ)
品番	製品名	製品コード	品番	製品名
CODE NO. (OLD)		DRAWN	DESIGNED	CHECKED
		W.Y.AHN 19.01.25	W.Y.AHN 19.01.25	H.S.KIM 19.01.25
		APPROVED		
		H.S.KIM 19.01.25		
		RELEASED		
		ENG 19.01.25 DEPT		

DRAWING NO.
JDC4-632766-80

SCALE
FREE

UNITS
mm

HRS HIROSE KOREA CO.,LTD.

PART NO.
KFL2-2LP-04H1T-A-100 (800)

CODE NO
CL6345-0148-7-800

1/1