Apr.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



HRS DRAWING FOR REFERENCE

2 STYLE AND DIMENSION OF REEL



Detail of part No. Label



NOTE 1. 1RL:15000 CONTACTS.
2 STYLE OF REEL AND BOX ARE SHOWN IN FIGURE.
3. A MAXIMUM OF 5 REELS ARE PACKED UP IN ONE BOX.
4. PLEASE BE SURE TO CHECK THE FORM OF CRIMPING USING A CABLE. WHEN YOU ADJUST APPLICATOR.
5 TIN PLATING AREA.
6 GOLD PLATING AREA.
7. THE DIMENSIONS IN PARENTHESIS ARE FOR REFERENCE.

NO.	MATERIAL	FINISH , REMARKS
1	PHOSPHOR BRONZE	CONTACT AREA : GOLD PLATING 0.2 μm MIN CARRIER/BARREL AREA : TIN PLATING 1 μm MIN OTHERS : NICKEL PLATING 0.5 μm MIN

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	10 : 1					

HRS HIROSE ELECTRIC CO., LTD.

APPROVED	KI. AKIYAMA	12. 01. 20
CHECED	MN. KENJO	12. 01. 20
DESIGNED	TO. HORII	12. 01. 20
DRAWN	TO. HORII	12. 01. 20

DRAWING NO.	EDC3-339722-00
PART NO.	DF62-EP2428PCFA
CODE NO.	CL544-0501-1-00

1/1