

May.1.2026 Copyright 2026 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE	
△					△					
△					△					
<b>APPLICABLE STANDARD</b>										
<b>RATING</b>	ELECTRIC SOURCE	PHASE	AC/DC	V	Hz	WEIGHT		0.5 kg		
	DISSIPATION POWER					APPLICABLE CONNECTOR	DF62-30SCA	544-0528-8		
	AIR SOURCE						DF62-EP30PCA	544-0531-2		
	AIR CONSUMPTION						DF62-30SC	544-0574-5		
	OPERATING TEMPERATURE LIMIT	°C ~ °C				APPLICABLE CABLE	UL1061 AWG30			
							APPLICABLE EQUIPMENT			
<b>SPECIFICATIONS</b>										
<b>CONSTITUTION</b>	<b>ITEM</b>	<b>TEST METHOD</b>				<b>REQUIREMENTS</b>		<b>QT</b>	<b>AT</b>	
	APPEARANCE, STRUCTURE AND FINISH	Visually and by measuring instrument.				According to drawing.		○	○	
	MARKING	Confirmed visually.				According to drawing.		○	○	
<b>REMARKS</b>						<b>DRAWN</b>	<b>DESIGNED</b>	<b>CHECKED</b>	<b>APPROVED</b>	<b>RELEASED</b>
						14.6.17 H.KUDO	14.6.17 M.TAKAHASHI	14.6.18 S. Ohtani	14.6.18 T. Ito	
Unless otherwise specified, refer to										
Note    QT:Qualification Test    AT:Assurance Test    X:Applicable Test										
<b>HRS</b> HIROSE ELECTRIC CO.,LTD.						<b>SPECIFICATION SHEET</b>		<b>PART NO.</b> HT801/DF62-30(10)		
<b>CODE NO. (OLD)</b>				<b>DRAWING NO.</b> ELC4- 276271-10		<b>CODE NO.</b> CL 550-0402-1-10			1	1

FROM001-1

