

APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C(NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C(NOTES 3)						
	OPERATING HUMIDITY RANGE	20% TO 80%(NOTES 2)	STORAGE HUMIDITY RANGE	40% TO 70%(NOTES 2)(NOTES 3)						
	VOLTAGE		APPLICABLE CONNECTOR	DF81※-40S-0.4H(##)						
	CURRENT		APPLICABLE CABLE							
SPECIFICATIONS										
ITEM		TEST METHOD		REQUIREMENTS						
QT		AT								
CONSTRUCTION										
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.						
MARKING		CONFIRMED VISUALLY.								
X		X								
X		X								
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED		DATE		
△										
REMARKS NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT NOTE2: NON CONDENSING NOTE3: THE TERM "STORAGE" REFERS TO PRODUCTS STORED FOR A LONG PERIOD PRIOR TO MOUNTING AND USE. THE OPERATING TEMPERATURE AND HUMIDITY RANGE COVERS THE NON-CONDUCTING CONDITION OF CONNECTORS AFTER BOARD MOUNTING AND THE TEMPORARY STORAGE CONDITIONS OF TRANSPORTATION, etc  Unless otherwise specified, refer to JIS C 5402,IEC60512.						APPROVED	MH. YAMANE		13. 11. 06	
						CHECKED	MH. TSUCHIDA		13. 11. 05	
						DESIGNED	AH. MIYAZAKI		13. 11. 01	
						DRAWN	AH. MIYAZAKI		13. 11. 01	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC4-345355-02				
HRS		SPECIFICATION SHEET		PART NO.		DF81-40P-LCH (52)				
		HIROSE ELECTRIC CO., LTD.		CODE NO.		CL662-8109-9-52		△ 1/1		