Jun.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

HRS DRAWING FOR REFERENCE



5 FIGURE OF INSERTION

HORIZONTAL: OK



DIAGONAL : NG



2 STYLE AND DIMENSION OF BOX



2 STYLE AND DIMENSION OF REEL



DETAIL OF PART No. LABEL



NOTE 1. 1RL:40000 CONTACTS.
2 STYLE OF REEL AND BOX IS SHOWN IN FIGURE ABOVE.
3. A MAXIMUM OF 5 REELS ARE PACKED UP IN ONE BOX.
4. PLEASE BE SURE TO CHECK THE FORM OF CRIMPING USING A CABLE. WHEN YOU ADJUST APPLICATOR.
5 AVOID ANGLED INSERTION OF CRIMP CONTACT(DF57-2830SCFA) INTO HOUSING FOR MAINTAINING PERFORMANCE RELIABILITY.

NO.	MATERIAL	FINISH , REMARKS
1	PHOSPHOR BRONZE	CONTACT AREA:GOLD PLATING 0.2μmMIN CARRIER AREA:TIN PLATING 1μmMIN UNDER PLATING:NICKEL PLATING 2μmMIN

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	20 : 1					

HIROSE ELECTRIC CO., LTD.

APPROVED	KI. AKIYAMA	14. 07. 31
CHECED	TS. FUKUSHIMA	14. 07. 30
DESIGNED	TS. MIYAKI	14. 07. 30
DRAWN	TS. MIYAKI	14. 07. 30

DRAWING NO.	EDC3-346818-00
PART NO.	DF57-2830SCFA
CODE NO.	CL666-0034-3-00

1/1

FORM HC0011-5-7_AN