

APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85°C (NOTE1)		STORAGE TEMPERATURE RANGE	-10 °C TO +60°C (NOTE3)		
	OPERATING HUMIDITY RANGE	20% TO 80% (NOTE2)		STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3)		
	APPLICABLE CONNECTOR	DF57H-2S-1.2C(##) DF57AH-2S-1.2C(##)		UL C-UL RATING △2	OPERATING TEMPERATURE RANGE	-35 °C TO +75°C (NOTE1)	
	APPLICABLE CONTACT	DF57-****SCF(##)			VOLTAGE	29 V AC/DC	
	VOLTAGE	50 V AC/DC			CURRENT	AWG26 : 3.0A/PIN AWG28 : 2.5A/PIN AWG30 : 1.5A/PIN AWG32 : 1.2A/PIN AWG34 : 1.0A/PIN	
	CURRENT	AWG26 : 3.0A/PIN AWG28 : 2.5A/PIN AWG30 : 1.5A/PIN AWG32 : 1.0A/PIN AWG34 : 0.8A/PIN					
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT	AT
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X
MARKING		CONFIRMED VISUALLY.				X	X
ELECTRIC CHARACTERISTICS							
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20mV MAX, 1mA (DC or 1000Hz).		10 mΩ MAX.		X	—
INSULATION RESISTANCE		100 V DC.		100 MΩ MIN.		X	—
VOLTAGE PROOF		500 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X	—
MECHANICAL CHARACTERISTICS							
MECHANICAL OPERATION		30 TIMES INSERTION AND EXTRACTION.		1)CONTACT RESISTANCE: 20 mΩ MAX. 2)NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
CONTACT INSERTION AND EXTRACTION FORCES		IT TAKES OUT AND INSERTS WITH A CONFORMITY CONNECTOR.		1)INSERTION FORCE : 20.0N MAX. 2)EXTRACTION FORCE: 0.9N MIN.		X	—
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 10 CYCLES FOR 3 DIRECTION.		1)NO ELECTRICAL DISCONTINUITY OF 1 μ s. 2)NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				X	—
ENVIRONMENTAL CHARACTERISTICS							
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2°C, 90 TO 95 %, 96 h. (AFTER LEAVING THE ROOM TEMPERATURE FOR 1-2h.)		1)CONTACT RESISTANCE: 20 mΩ MAX. 2)INSULATION RESISTANCE: 100 MΩ MIN. 3)NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55°C→ +85°C TIME 30min→ 30min UNDER 5 CYCLES. (THE TRANSFERRING TIME OF THE TANK IS 2-3 min) (AFTER LEAVING THE ROOM TEMPERATURE FOR 1-2h.)		1)CONTACT RESISTANCE: 20 mΩ MAX. 2)INSULATION RESISTANCE: 100 MΩ MIN. 3)NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	—
RESISTANCE TO SOLDERING HEAT		1) REFLOW SOLDERING « REFLOW TIME » NUMBER OF REFLOW CYCLES : 2 CYCLES MAX. DURATION ABOVE 220 °C, 60 sec. MAX. PEAK TEMPERATURE: 250°C 10 sec. MAX. « PRE-HEAT TIME » PRE-HEAT TEMPERATURE(MIN) :150 °C PRE-HEAT TEMPERATURE(MAX) :180 °C PRE-HEAT TIME(MIN) : 90 sec. PRE-HEAT TIME(MAX) : 120 sec. 2) MANUAL SOLDERING SOLDERING IRON TEMPERATURE :350±10°C, SOLDERING TIME : 3sec. NO STRENGTH ON CONTACT.		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		X	—
SOLDERABILITY		SOLDERING TEMPERATURE : 245°C DURATION OF IMMERSION :SOLDERING, FOR 5 sec.		NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.		X	—
NOTE1:INCLUDE THE TEMPERATURE RISING BY CURRENT. NOTE2:NO CONDENSING. NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE MOUNTED ON PCB. AFTER MOUNTED ON PCB, OPERATION TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.							
	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE	
△2	1	DIS-H-00005747		HK. HAYASHI	SZ. ONO	20200217	
REMARKS Unless otherwise specified, refer to IEC 60512.					APPROVED	KI. AKIYAMA	20120319
					CHECKED	HK. UMEHARA	20120319
					DESIGNED	TS. KUMAZAWA	20120319
					DRAWN	TS. KUMAZAWA	20120319
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO.		ELC-343904-21-01	
HRS	SPECIFICATION SHEET			PART NO.	DF57H-2P-1. 2V (21)		
	HIROSE ELECTRIC CO., LTD.			CODE NO.	CL666-0104-7-21	△	1/1